

## Term Project - Fall 2022 The Leaning Tower of Pisa: Settlement calculations

The construction of the Leaning Tower of Pisa began in 1173 and due to two long breaks, it went on for 176 years. Those breaks were most likely caused by political events. The first break came in 1178, and by that time, the construction work had only reached the 4<sup>th</sup> order of the final Tower, which is illustrated in Figure 1.



## Figure 1: Cross-section of the Tower (Burland, Jamiolkowski, & Viggiani, 2009)

The second break came in 1278 after the tower had reached the 7th order of the finished Tower. Completion with the rise of the bell Tower was first achieved in 1360 and although completion would have taken almost 15% of the time had it not been for the two shutdowns, these have actually proven to be crucial for the Tower Existence. Had they built the Tower, giving it no time to consolidate, the weight of the Tower would have caused an undrained bearing capacity failure

This content is protected and may not be shared, uploaded, or distributed.

in the underlying soil and the Tower would have been history already after the first construction phase.

By the time of the final stage of construction, the tower had already leaned significantly, as evidenced by the changed centerline direction of the 8<sup>th</sup> order, that was added last.

The dimensions of the Tower are shown in Figure 1. The diameter of the foundation is 19.6 m and the total weight of the tower at the end of construction is 141,640 kN (~142MN) resulting in an average foundation pressure of  $q = \frac{141640kN}{\pi(\frac{19.6}{2})^2m^2} = 469kPa$  (rounded up as 500 kPa in Figure 1).



Figure 2 Geology of the subsoil beneath the Tower (Leoni & Vermeer, 3D creep analysis of the Leaning Tower of Pisa, 2002)

# **Term Project - Phase 1:**

The soil underneath the Tower can be divided into three distinct layers – horizon A, horizon B, and horizon C, which are illustrated in Figure 2. One sample collected from Horizon A (A1+A2) and four samples collected from Horizon B (B1-B3, B4+B5, B6, B7-B10), were sent to the laboratory for testing. Horizon C consists of dense sand, which extends to a considerable depth (Kristiansen, 2012). Grain size distribution, Atterberg Limits tests, and proctor compaction tests were conducted on those samples. Below are the results from those tests:

	Mass of the sample retained on the sieve								
Sieve Number	Layer 1	Layer 2	Layer 3	Layer 4	Layer 5				
	A1-A2	B1-B3	B4-B5	B6	B7-B10				
4	0	0	0	0	0				
10	22	10	13	149	14				
20	50	9	19	161	14				
40	103	8	9	234	23				
60	90	11	23	211	12				
100	95	12	17	287	13				
200	60	16	12	187	11				
Pan	30	125	102	56	123				
Liquid Limit	55	65	45	55	55				
Plastic Limit	Plastic Limit 40		20	40	21				

#### **Grain Size Distribution and Atterberg Limits:**

## **Proctor Compaction Test Results:**

Layer 1		Layer 2		Layer 3		Layer 4		Layer 5	
A1-A2		B1-B3		B4-B5		B6		B7-B10	
	Weight								
	of the								
Water	mold								
Content	+wet								
(%)	soil (lb)								
13	9.78	62	9.17	23	9.98	9	9.60	38	9.77
14	9.87	63	9.32	24	10.05	10	9.72	39	9.85
15	9.96	64	9.42	25	10.16	11	9.82	40	10.08
16	9.96	65	9.56	26	10.11	12	9.93	41	9.93
17	9.96	66	9.51	27	10.07	13	9.90	42	9.93
18	9.91	67	9.39	28	10.05	14	9.88	43	9.90

Weight of the mold = 5.7 lbs ; Volume of the mold = 1/30 ft<sup>3</sup>

This content is protected and may not be shared, uploaded, or distributed.

## Assignment:

- 1. Plot the Grain Size Distribution Curves and classify the soil samples according to USCS.
- 2. Determine the Maximum Dry Unit Weight of the five samples.
- 3. Determine the Optimum Moisture Content of the five samples.

Deliverables for Phase 1:

- 1. An Excel spreadsheet showing all calculations as mentioned in the 'Assignment' section.
- 2. The group formation is handled separately using CATME (you should have received an email with a survey link by now).
- 3. Due date: 10/21/2022 by 11:59 PM

## References

Kristiansen, M. 2012 An under-excavation model for The Leaning Tower of Pisa, MS Thesis, Norwegian University of Science and Technology.

Leoni, M., & Vermeer, P. A. (2002). 3D creep analysis of the Leaning Tower of Pisa. Stuttgart: Institute of Geotechnical Engineering Stuttgart.

Mesri, G., Heiden, J.E., Shahien, M., 1997a. Geotechnical characteristics and compression of pisa clay. In: Proceedings of the 14th International Conference on Soil Mechanics and Foundation Engineering, Hamburg, Germany. pp. 373–376.

Mitchell, J.K., Vivatrat, V., and Lambe, W.T. 1977. Foundation performance of the Tower of Pisa. Journal of the Geotechnical Engineering Division, ASCE, 103(GT3): 227–249.

Burland, J. B., Jamiolkowski, M. B., & Viggiani, C. (2009, July 01). Leaning Tower of Pisa: Behaviour after Stabilization Operations . International Journal of Geoengineering Case Histories , ss. 156-169.